

HANGER-MATE® FOR STEEL

HANGER-MATE FOR STEEL - INTERNALLY THREADED - VERTICAL

CAT #	ROD DIA	DESCRIPTION	CTN	MSTR	SOCKET SIZE	DRIVER
PFM2231000	1/4"	1/4"-20 x 1" #3	25	125	1/2"	PFM2201200
PFM2231100	3/8"	1/4"-20 x 1" #3	25	125	1/2"	PFM2201200
PFM223110N	3/8"	1/4"-20 x 1" #3 w/ Nut	25	125	1/2"	PFM2201200
PFM2231150	3/8"	1/4"-20 x 1-1/2" #5	25	125	1/2"	PFM2201200
PFM223115N	3/8"	1/4"-20 x 1-1/2" #5 w/ Nut	25	125	1/2"	PFM2201200
PFM2231200	3/8"	1/4"-20 x 1-1/2" #3	25	125	1/2"	PFM2201200
PFM223120N	3/8"	1/4"-20 x 1-1/2" #3 w/ Nut	25	125	1/2"	PFM2201200
PFM2231250	3/8"	1/4"-20 x 2" #3	25	125	1/2"	PFM2201200



HANGER-MATE FOR STEEL - INTERNALLY THREADED - HORIZONTAL

CAT #	ROD DIA	DESCRIPTION	CTN	MSTR	SOCKET SIZE	DRIVER
PFM2241100	3/8"	1/4"-20 x 1" #3	25	125	1/2"	PFM2201200
PFM224110N	3/8"	1/4"-20 x 1" 3 w/ Nut	25	125	1/2"	PFM2201200
PFM2241150	3/8"	1/4"-20 x 1-1/2" #3	25	125	1/2"	PFM2201200
PFM224115N	3/8"	1/4"-20 x 1-1/2" #3 w/ Nut	25	125	1/2"	PFM2201200
PFM2241200	3/8"	1/4"-20 x 1-1/2" #5	25	125	1/2"	PFM2201200
PFM224120N	3/8"	1/4"-20 x 1-1/2" #5 w/ Nut	25	125	1/2"	PFM2201200



HANGER-MATE FOR STEEL - INTERNALLY THREADED - PIVOT

CAT #	ROD DIA	DESCRIPTION	CTN	MSTR	DRIVER
PFM2281150	3/8"	1/4"-20 x 1" #3	25	125	PFM2201250
PFM2281200	3/8"	1/2"-20 x 1-3/4" #5	25	125	PFM2201250
PFM2281250	3/8"	1/4"-14 x 1" #3	25	125	PFM2201250



HANGER-MATE FOR STEEL - CEILING SCREW EYELET

CAT #	HOLE DIA	DESCRIPTION	CTN	MSTR	DRIVER
PFM2231500	3/8"	1/4" x 2"	25	125	PFM2201350
PFM2231550	3/8"	1/4" x 3-1/4"	25	125	PFM2201350



INSTALLATION DRIVERS AND ACCESSORIES

HANGER-MATE FOR STEEL - INTERNALLY THREADED - VERTICAL

CAT #	SOCKET SIZE	DRIVE	CTN	MSTR
PFM2201200	1/2"	1/4" Hex	5	25



HANGER-MATE FOR STEEL - INTERNALLY THREADED - HORIZONTAL

CAT #	SOCKET SIZE	DRIVE	CTN	MSTR
PFM2201200	1/2"	1/4" Hex	5	25



HANGER-MATE FOR STEEL - INTERNALLY THREADED - PIVOT

CAT #	DRIVE	CTN	MSTR
PFM2201250	1/4" Hex	5	25



HANGER-MATE FOR STEEL - CEILING SCREW EYELET

CAT #	DRIVE	CTN	MSTR
PFM2201350	1/4" Hex	5	25



HANGER-MATE FOR STEEL - OTHER ACCESSORIES

CAT #	DESCRIPTION	CTN	MSTR
PFM2201050	3/8" to 1/2" Adaptor ¹	25	125
PFM2201100	Hangermate Pole Tool Kit ²	25	125



1. The 3/8" to 1/2" adaptor has a 3/8-16 external thread and a 1/2-13 internal thread.

2. The Hangermate pole tool kit is designed for use with standard 1/2" steel conduit tubing (conduit not included) and can be customized to various lengths and ceiling heights. Compatible with standard steel and wood Hangermate.

RECOMMENDED INSTALLATION POWER TOOLS

HANGER-MATE FOR STEEL

CAT #	TYPE
DCF887D2	Cordless Impact Driver



SUSPENDER® FOR STEEL

SUSPENDER FOR STEEL - DUAL-DIRECTION

CAT #	ROD DIA	DESCRIPTION	CTN	MSTR	DRIVER
PFM227110N	3/8"	1/4"-20 x 1" #3 w/ Nut	25	125	PFM2201300
PFM227120N	3/8"	1/4"-29 x 1-1/2" #3 w/ Nut	25	125	PFM2201300
PFM227130N	3/8"	1/4"-20 x 1-1/2" #5 w/ Nut	25	125	PFM2201300



INSTALLATION DRIVERS AND ACCESSORIES

SUSPENDER FOR STEEL - DUAL-DIRECTION

CAT #	DRIVE	CTN	MSTR
PFM2201300	1/4" Hex	5	25



HANGERMATE FOR STEEL - OTHER ACCESSORIES

CAT #	DESCRIPTION	CTN	MSTR
PFM2201050	3/8" to 1/2" Adaptor ¹	25	125
PFM2201100	Hangermate Pole Tool Kit ²	25	125



1. The 3/8" to 1/2" adaptor has a 3/8-16 external thread and a 1/2-13 internal thread.
2. The Hangermate pole tool kit is designed for use with standard 1/2" steel conduit tubing (conduit not included) and can be customized to various lengths and ceiling heights. Compatible with standard steel and wood Hangermate.

RECOMMENDED INSTALLATION POWER TOOLS

SUSPENDER FOR STEEL

CAT #	TYPE
DCF887D2	Cordless Impact Driver



ANCHOR

INSTALLATION

APPROVALS

HANGERMATE® FOR STEEL SYSTEMS

HANGERMATE FOR STEEL - INTERNALLY THREADED - VERTICAL

CAT #	HANG	ROD DIA.	DESCRIPTION
PFM2231000	Vertical	1/4"	1/4"-20 x 1" #3
PFM2231100	Vertical	3/8"	1/4"-20 x 1" #3
PFM223110N	Vertical	3/8"	1/4"-20 x 1" #3 w/ Nut
PFM2231150	Vertical	3/8"	1/4"-20 x 1-1/2" #5
PFM223115N	Vertical	3/8"	1/4"-20 x 1-1/2" #5 w/ Nut
PFM2231200	Vertical	3/8"	1/4"-20 x 1-1/2" #3
PFM223120N	Vertical	3/8"	1/4"-20 x 1-1/2" #3 w/ Nut
PFM2231250	Vertical	3/8"	1/4"-20 x 2" #3

SOCKET SIZE	DRIVER	MIN. THICKNESS	MAX. THICKNESS	LOAD DIRECTION
1/2"	PFM2201200	0.060"	0.210"	Vertical
1/2"	PFM2201200	0.060"	0.210"	Vertical
1/2"	PFM2201200	0.125"	0.500"	Vertical
1/2"	PFM2201200	0.125"	0.500"	Vertical
1/2"	PFM2201200	0.060"	0.210"	Vertical
1/2"	PFM2201200	0.060"	0.210"	Vertical
1/2"	PFM2201200	0.060"	0.210"	Vertical

UL		FM	
PIPE SIZE	THICK.	PIPE SIZE	THICK
-	-	-	-
4"	0.060"	-	-
4"	0.125"	4"	0.105"
4"	0.060"	4"	0.060"
4"	0.125"	4"	0.105"
4"	0.060"	-	-
4"	0.060"	-	-
4"	0.125"	-	-

HANGERMATE FOR STEEL - INTERNALLY THREADED - HORIZONTAL

CAT #	HANG	ROD DIA.	DESCRIPTION
PFM2241100	Horizontal	3/8"	1/4"-20 x 1" #3
PFM224110N	Horizontal	3/8"	1/4"-20 x 1" 3 w/ Nut
PFM2241150	Horizontal	3/8"	1/4"-20 x 1-1/2" #3
PFM224115N	Horizontal	3/8"	1/4"-20 x 1-1/2" #3 w/ Nut
PFM2241200	Horizontal	3/8"	1/4"-20 x 1-1/2" #5
PFM224120N	Horizontal	3/8"	1/4"-20 x 1-1/2" #5 w/ Nut

SOCKET SIZE	DRIVER	MIN. THICKNESS	MAX. THICKNESS	LOAD DIRECTION
1/2"	PFM2201200	0.060"	0.210"	Horizontal
1/2"	PFM2201200	0.060"	0.210"	Horizontal
1/2"	PFM2201200	0.060"	0.210"	Horizontal
1/2"	PFM2201200	0.060"	0.210"	Horizontal
1/2"	PFM2201200	0.125"	0.500"	Horizontal
1/2"	PFM2201200	0.125"	0.500"	Horizontal

UL		FM	
PIPE SIZE	THICK.	PIPE SIZE	THICK
-	-	-	-
4"	0.060"	4"	0.060"
-	-	-	-
4"	0.060"	4"	0.060"
-	-	-	-
4"	0.060"	4"	0.060"

HANGERMATE FOR STEEL - INTERNALLY THREADED - PIVOT

CAT #	HANG	ROD DIA.	DESCRIPTION
PFM2281150	Variable	3/8"	1/4"-20 x 1" #3
PFM2281200	Variable	3/8"	1/2"-20 x 1-3/4" #5
PFM2281250	Variable	3/8"	1/4"-14 x 1" #3

DRIVER	MIN. THICKNESS	MAX. THICKNESS	LOAD DIRECTION
PFM2201250	0.060"	0.188"	Vertical 45°
PFM2201250	0.125"	0.500"	Vertical 45°
PFM2201250	0.060"	0.188"	Vertical 45°

UL		FM	
PIPE SIZE	THICK.	PIPE SIZE	THICK
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

HANGERMATE FOR STEEL - CEILING SCREW EYELET

CAT #	HANG	ROD DIA.	DESCRIPTION
PFM2231500	-	3/8"	1/4" x 2"
PFM2231550	-	3/8"	1/4" x 3-1/4"

DRIVER	MIN. THICKNESS	MAX. THICKNESS	LOAD DIRECTION
PFM2201350	0.060"	0.105"	-
PFM2201350	0.06	0.105"	-

UL		FM	
PIPE SIZE	THICK.	PIPE SIZE	THICK
-	-	-	-
-	-	-	-

SUSPENDER® FOR STEEL SYSTEMS

SUSPENDER FOR STEEL - DUAL-DIRECTION

CAT #	HANG	ROD DIA.	DESCRIPTION
PFM227110N	Vertical and Horizontal	3/8"	1/4"-20 x 1" #3 w/ Nut
PFM227120N	Vertical and Horizontal	3/8"	1/4"-29 x 1-1/2" #3 w/ Nut
PFM227130N	Vertical and Horizontal	3/8"	1/4"-20 x 1-1/2" #5 w/ Nut

DRIVER	MIN. THICKNESS	MAX. THICKNESS	LOAD DIRECTION
PFM2201300	0.060"	0.188"	Vertical Horizontal
PFM2201300	0.125"	0.500"	Vertical Horizontal
PFM2201300	0.060"	0.188"	Vertical Horizontal

UL		FM	
PIPE SIZE	THICK.	PIPE SIZE	THICK
4"	0.060"	4"	0.060"
4"	0.060"	4"	0.060"
4"	0.060"	4"	0.060"
4"	0.060"	4"	0.060"
4"	0.060"	4"	0.060"